

## MIS-65 & MIS-100

### Wraparound Sleeves for Offshore Pipeline Joints

MIS heat shrinkable sleeve series provides superior direct-to-pipe corrosion protection for offshore pipeline joints. These products have been specifically developed to meet the demanding offshore installation times while providing consistent joint-to-joint performance and easily enduring harsh infill operations.

#### Robust and Reliable

- Crosslinked polyethylene backing works with purpose engineered adhesive to provide tight seal against corrosion at the pipe surface
- Adhesive is compatible with a variety of mainline coatings including Asphalt Enamel, Coal Tar Enamel, 3LPP, 3LPE, FBE and Tape

#### Infill Ready

- MIS shrink sleeves are designed to be used with lay barge applied infill systems including PU foam and solid PU and withstand high temperatures associated with the infill processes
- The MIS sleeve systems provide long term corrosion protection for pipelines operating up to 100°C

#### Maximize Cost Savings

- One-piece sleeve construction with pre-attached closure reduces installation time thus resulting in high production rates
- Low preheat adhesives result in fast pipe preparation and reliable sleeve application



#### Applications



Offshore Pipelines



Oil & Gas



Infill Systems



Reel, J & S Lay



Girth-Weld Joints



# MIS-65 & MIS-100

## Wraparound Sleeves for Offshore Pipeline Joints

Sleeve Operating Characteristics		MIS-65	MIS-100	
Maximum Operating Temperature		65°C	100°C	
Minimum Installation Temperature		65°C	90°C	
Mainline Coating Compatibility		Bitumen, Tape, CTE, FBE, PE	Bitumen, Tape, CTE, FBE, PE	
Adhesive Properties		Standard	Typical Value	
Softening Point	ASTM E28	85°C	121°C	
Lap Shear @ 23°C	ISO 21809-3	20 N/cm <sup>2</sup>	40 N/cm <sup>2</sup>	
Backing Properties				
Tensile Strength	ASTM D638	24 MPa	24 MPa	
Elongation	ASTM D638	600%	600%	
Hardness - Shore D	ASTM D2240	57	57	
Dielectric Strength	ASTM D149	35 kV/mm	35 kV/mm	
Volume Resistivity	ASTM D257	10 <sup>18</sup> ohm-cm	10 <sup>18</sup> ohm-cm	
Water Absorption	ASTM D570	0.05%	0.05%	
Sleeve Properties				
Adhesion Strength @ 23°C	ISO 21809-3	22 N/cm	60 N/cm	
Impact Resistance	ISO 21809-3	≥ 5 J/mm	≥ 7 J/mm	
Indentation Resistance	ISO 21809-3	Pass	Pass	
Cathodic Disbondment @ 23°C	ISO 21809-3	10 mm	10 mm	
Thickness		T	L	S
Backing Thickness		0.035"	0.035"	0.045"
Adhesive Thickness		0.035"	0.045"	0.060"



The product information shown here is intended as a guide for standard products.

Consult your Canusa representative for specific projects or unique applications.

**Canusa-CPS**  
A division of Shawcor Ltd.

#### Head Office

25 Bethridge Road  
Toronto, ON, Canada M9W 1M7  
Tel: +1 416 743 7111  
Fax: +1 416 743 5927

#### Canada

Dome Tower St. 2200, 333-7th Avenue SW  
Calgary, AB, Canada T2P 2Z1  
Tel: +1 403 218 8207  
Fax: +1 403 264 3649

#### Americas

5875 N. Sam Houston Pkwy W., Suite 200  
Houston, TX, USA 77086  
Tel: +1 281 886 2350  
Fax: +1 281 886 2353

#### Middle East

ADPC - Mussafah Port, P.O. Box 2621  
Abu Dhabi, UAE  
Tel: +971 2 496 3500  
Fax: +971 2 496 3501

#### Europe, Africa & Russia

Dellaertweg 9-E, Gebouw "Le Carrefour"  
2316 WZ Leiden, The Netherlands (NL)  
Tel: +31 71 80 802 70  
Fax: +31 71 80 802 71

#### Asia-Pacific

101 Thomson Road, #11-03 United Square  
307591 Singapore  
Tel: +65 6749 8918  
Fax: +65 6749 8919

**Quality Management system**  
registered to ISO 9001

Canusa warrants that the product conforms to its chemical and physical description and is appropriate for the use stated on the product data sheet when used in compliance with Canusa's written instructions. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith. Canusa's liability is stated in the standard terms and conditions of sale. Canusa makes no other warranty either expressed or implied. All information contained in this data sheet is to be used as a guide and is subject to change without notice. This data sheet supersedes all previous data sheets on this product. E&OE

PDS\_MIS65 & MIS100\_rev016

Since 1967, Canusa-CPS has been a leading developer and manufacturer of specialty pipeline coatings for the sealing and corrosion protection of pipeline joints and other substrates. Canusa-CPS high performance products are manufactured to the highest quality standards and are available in a number of configurations to accommodate many specific project applications.